

Stationary 6.5 Peak HP 60 Gallon Air Compressor

Product Features:

- Thermally protected US Motor® 6.5 peak HP motor with reset
- 2 cylinder cast iron single stage oil lubricated pump
- 150 PSI Max pressure for optimum tool performance
- 60 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Belt drive with sturdy metal belt guard
- Large intake "Auto-Drop" metal filters
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- High efficiency reed valves for maximum performance



MODEL	KC-6160V3
MOTOR (PEAK)	6.5 HP
FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)	95-125 PSI (Max. 130 PSI)
AIR DELIVERY @ 40 PSI	13.4 CFM
AIR DELIVERY @ 90 PSI	11.2 CFM
TANK SIZE	60 Gallon
MOTOR AMPERAGE	15 Amp.
RPM	3,450
VOLTAGE	240V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	25" x 22" x 67" / 260 lbs
PACKAGE DIMENSIONS (LxWxH) / WEIGHT	31" x 24" x 73" / 270 lbs
UPC	7 72995 01080 6