

## 28" Gearhead Drilling Machine (550V, 3 Phase)

### Product Features:

- Powerful 2 HP motor, provides ample power for production drilling
- Magnetic line interruption switch and safety guard with limit switch protection
- Quill has an internal MT #4 to accept tapered drill press accessories
- Feed selector dial and automatic power downfeed lever and tapping
- Production sized table with coolant trough and clamping slots
- Positive depth stop for quick and easy adjustment
- Built-in tool ejector
- Magnetic line interruption switch and safety guard with limit switch protection
- Comes with 5/8" (JT#33) drill chuck, chuck key, MT#4 chuck arbor, MT#4-MT#2 sleeve, MT#4-MT#3 sleeve, recirculating coolant system, work light, retractable transparent guard, drift key and tool box



MODEL	KC-50
DRILLING CAPACITY IN LIGHT ALLOY STEEL	1-3/8"
DRILLING CAPACITY IN MILD STEEL	1-1/2"
CHUCK SIZE	5/8"
SPINDLE TAPER	MT #4
SWING	27-1/2"
STROKE	7"
MAX. DISTANCE SPINDLE TO TABLE	26"
MAX. DISTANCE SPINDLE TO BASE	43"
TABLE DIMENSIONS	22" x 22"
SIZE OF T-SLOT ON TABLE	5/8"
SPEEDS	18 (60 -1,740) RPM
MOTOR	2.4 Amp.
COOLANT PUMP MOTOR	1/8 HP
VOLTAGE	550V, 3 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	22" x 37" x 91" / 1,200 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	83-3/4" x 24-7/8" x 44-1/4" / 1,309 lbs
UPC	7 72995 00478 2