

## High Output 6.5 Peak HP 60 Gallon Air Compressor

### Product Features:

- Thermally protected US Motors® 6.5 peak HP motor with reset
- 3 cylinder cast iron single stage oil lubricated pump
- High output 18.5 CFM @ 100 PSI
- 150 PSI Max pressure for optimum tool performance
- 60 Gallon ASME registered tank provides longer run times
- ASME safety valve
- Belt drive with sturdy enclosed metal belt guard
- Large intake filters
- Heavy-duty 1/2" ball valve and easy to read tank pressure gauge
- Pump with "V" style design minimizes vibrations, improves cooling and extends compressor life
- High efficiency reed valves for maximum performance



<b>MODEL</b>	<b>KC-5160V3</b>
<b>MOTOR (PEAK)</b>	6.5 HP
<b>FACTORY PRESSURE SETTING (ADJUSTABLE UP TO)</b>	95-125 PSI (Max 135 PSI)
<b>MAXIMUM PRESSURE</b>	150 PSI
<b>AIR DELIVERY @ 40 PSI</b>	22.6 CFM
<b>AIR DELIVERY @ 100 PSI</b>	18.5 CFM
<b>TANK SIZE</b>	60 Gallon
<b>MOTOR AMPERAGE</b>	23 Amp.
<b>RPM</b>	3,450
<b>VOLTAGE</b>	240V, 1 Phase, 60 Hz
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	25" x 22" x 68" / 280 lbs
<b>PACKAGE DIMENSIONS (LxWxH) / WEIGHT</b>	31" x 24" x 73" / 290 lbs
<b>UPC</b>	7 72995 01100 1