

# Milling Drilling Machine



## Product Features:

- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle is equipped with four heavy-duty tapered roller bearings
- Table control hand wheels have large micrometer dials graduated in .001"
- Head swivels 360° and is easily raised and lowered
- Comes with 3" face cutter, 1/2" chuck with key, 3-1/2" angle vise and safety guard

<b>MODEL</b>	<b>PDM-30</b>
<b>DRILLING CAPACITY</b>	1-1/4"
<b>MAX. DIST. SPINDLE NOSE TO TABLE</b>	18-7/8"
<b>SWING</b>	16-1/2"
<b>SPINDLE TAPER</b>	R8
<b>SPINDLE STROKE</b>	5"
<b>DIAMETER OF COLUMN</b>	4-3/4"
<b>SPEEDS</b>	12 (150-2,500) RPM
<b>FACE MILL CAPACITY</b>	3"
<b>END MILL CAPACITY</b>	3/4"
<b>MAX. LONGITUDINAL TRAVEL</b>	17"
<b>CROSS TRAVEL</b>	7-1/4"
<b>WORKING AREA OF TABLE</b>	8-1/4" x 28-3/4"
<b>SIZE OF T-SLOT ON TABLE</b>	5/8"
<b>MOTOR</b>	11 Amp.
<b>VOLTAGE</b>	220V, 1 Phase, 60 Hz
<b>ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT</b>	43" x 39" x 42" / 502 lbs
<b>PACKAGING DIMENSIONS (LxWxH) / WEIGHT</b>	30-1/4" x 32" x 43-3/8" / 600 lbs
<b>UPC</b>	7 72995 30001 3