

Milling Drilling Machine With Digital Readouts

Product Features:

- Powerful 1 HP single phase DC motor
- Safety guard with limit switch protection
- Magnetic line interruption switch needs a restart after a power failure
- Spindle depth digital readout and control panel with metric and imperial readings
- Spindle RPM digital readout
- Spindle depth fine feed knob
- Forward/reverse switch and variable speed selector dials
- Comes with 1/2" chuck, chuck key, R8 chuck arbor, safety guard, 2 T-bolts, oil bottle, adjustment wrenches, hex. keys and tool box



MODEL	KC-20VS-2
DRILLING CAPACITY IN CAST-IRON	3/4"
DRILLING CAPACITY IN STEEL	5/8"
MAX. DISTANCE SPINDLE NOSE TO TABLE	13"
SWING	13"
SPINDLE TAPER	R8
SPINDLE STROKE	2"
VARIABLE SPEEDS	2 (50-1,125 / 100-2,250) RPM
FACE MILL CAPACITY	2-1/2"
END MILL CAPACITY	3/4"
MAX. LONGITUDINAL TRAVEL	18-7/8"
CROSS TRAVEL	6-7/8"
WORKING AREA OF THE TABLE	7-1/16" x 27-1/2"
SIZE OF T-SLOT ON TABLE	1/2"
MOTOR	4.8 Amp., 2,250 RPM
VOLTAGE	120V, 1 Phase, 60 Hz
ASSEMBLED DIMENSIONS (LxWxH) / WEIGHT	27-1/2" x 29-5/8" x 35-3/8" / 264 lbs
PACKAGING DIMENSIONS (LxWxH) / WEIGHT	17-1/2" x 16-1/2" x 32-1/2" / 308 lbs
UPC	7 72995 01009 7